



(IRM-60)



(IRM-60-xxST)



Features

- 3.43"x2.05"compact size
- PCB, chassis or screw terminal mounting version
- Universal input 85~305VAC
- No load power consumption<0.15W
- EMI Class B without additional components
- Wide operating temp. range -30~70°C
- Protections: Short circuit / Overload / Over voltage
- Cooling by free air convection
- Isolation Class II
- Over voltage category III
- Pass LPS(Except for 5V)
- 3 years warranty

Applications

- Industrial electrical equipment
- Mechanical equipment
- Factory automation equipment
- Handheld electronic device

GTIN CODE


MW Search: <https://www.meanwell.com/serviceGTIN.aspx>

Description

IRM-60 is a 60W miniature (87*52*29.5mm) AC-DC module-type power supply, ready to be soldered onto the PCB boards of various kinds of electronic instruments or industrial automation equipments. This product allows the universal input voltage range of 85~305VAC. The 94V-0 flame retardant plastic case and the fully-potted silicone enhance the heat dissipation. PCB mounting style model(Blank) meet the anti-vibration demand up to 2G and screw terminal style model (ST) meet the anti-vibration demand up to 5G; moreover, it provides the fundamental resistance to dust and moisture.

With the high efficiency up to 91% and the extremely low no-load power consumption below 0.15W, IRM-60 series fulfills the worldwide regulation for the low power consumption requirement for electronics. The entire series is a Class II design (no FG pin), incorporating the built-in EMI filtering components, enabling the compliance with BS EN/EN55032 Class B; the supreme EMC features keep the end electronic units from electromagnetic interference. In addition to the PCB mounting style model, IRM-60 series also offers the screw terminal style model (ST).


Model Encoding




SPECIFICATION

MODEL		IRM-60-5 □		IRM-60-12 □		IRM-60-15 □		IRM-60-24 □		IRM-60-48 □	
OUTPUT	DC VOLTAGE	5V		12V		15V		24V		48V	
	RATED CURRENT	10A		5A		4A		2.5A		1.25A	
	CURRENT RANGE	0 ~ 10A		0 ~ 5A		0 ~ 4A		0 ~ 2.5A		0 ~ 1.25A	
	RATED POWER	50W		60W		60W		60W		60W	
	RIPPLE & NOISE (max.) Note.2	80mVp-p		120mVp-p		120mVp-p		150mVp-p		240mVp-p	
	VOLTAGE TOLERANCE Note.3	± 2.5%		± 2.5%		± 2.5%		± 2.5%		± 2.5%	
	LINE REGULATION	± 0.5%		± 0.5%		± 0.5%		± 0.5%		± 0.5%	
	LOAD REGULATION	± 1.0%		± 1.0%		± 0.5%		± 0.5%		± 0.5%	
	SETUP, RISE TIME	1000ms, 30ms/230VAC 2000ms, 30ms/115VAC at full load									
	HOLD UP TIME (Typ.)	50ms/230VAC 12ms/115VAC at full load									
INPUT	VOLTAGE RANGE	85 ~ 305VAC									
	FREQUENCY RANGE	47 ~ 440Hz									
	EFFICIENCY (Typ.)	84%		87.5%		89%		90%		91%	
	AC CURRENT (Typ.)	1.8A/115VAC		1.0A/230VAC		0.9A/277VAC					
	INRUSH CURRENT (Typ.)	COLD START 30A/115VAC 60A/230VAC									
	LEAKAGE CURRENT	< 0.25mA/277VAC									
PROTECTION	OVERLOAD	115%~160% rated output power Protection type : Hiccup mode, recovers automatically after fault condition is removed									
	OVER VOLTAGE	5.25 ~ 6.75V		12.6 ~ 16.2V		15.75 ~ 20.25V		25.2 ~ 32.4V		50.4 ~ 64.8V	
		Protection type : Shut off o/p voltage, clamping by zener diode									
ENVIRONMENT	WORKING TEMP.	-30 ~ +70℃ (Refer to "Derating Curve")									
	WORKING HUMIDITY	20 ~ 90% RH non-condensing									
	STORAGE TEMP., HUMIDITY	-40 ~ +85℃, 10 ~ 95% RH									
	TEMP. COEFFICIENT	± 0.03%/℃ (0 ~ 50℃)									
	VIBRATION	Blank:10 ~ 500Hz, 2G 10min./1cycle, period for 60min. each along X, Y, Z axes ST:10 ~ 500Hz, 5G 10min./1cycle, period for 60min. each along X, Y, Z axes									
	SOLDERING TEMPERATURE	Wave soldering: 265℃, 5s (max.); Manual soldering: 390℃, 3s (max.)									
	OVER VOLTAGE CATEGORY	III ; According to EN62368-1; altitude up to 2000 meters									
	OPERATING ALTITUDE Note.4	2000 meters									
SAFETY & EMC (Note.5)	SAFETY STANDARDS	IEC62368-1, UL62368-1, TUV BS EN/EN62368-1, BS EN/EN60335-1, EAC TP TC 004, BSMI CNS14336-1 approved									
	WITHSTAND VOLTAGE	I/P-O/P:4KVAC									
	ISOLATION RESISTANCE	I/P-O/P:100M Ohms / 500VDC / 25℃ / 70% RH									
	EMC EMISSION	Parameter	Standard				Test Level / Note				
		Conducted	BS EN/EN55032(CISPR32), CNS13438				Class B				
		Radiated	BS EN/EN55032(CISPR32), CNS13438				Class B				
		Harmonic Current (Note 5)	BS EN/EN61000-3-2				Class A				
		Voltage Flicker	BS EN/EN61000-3-3				-----				
	EMC IMMUNITY	BS EN/EN55035, BS EN/EN61000-6-2									
		Parameter	Standard				Test Level /Note				
		ESD	BS EN/EN61000-4-2				Level 3, 8KV air; Level 2, 4KV contact, criteria A				
		Radiated Susceptibility	BS EN/EN61000-4-3				Level 3, criteria A				
		EFT/Burest	BS EN/EN61000-4-4				Level 3, criteria A				
		Surge	BS EN/EN61000-4-5				Level 4, 2KV/L-N, criteria A				
		Conducted	BS EN/EN61000-4-6				Level 3, criteria A				
		Magnetic Field	BS EN/EN61000-4-8				Level 4, criteria A				
Voltage Dips and interruptions		BS EN/EN61000-4-11				> 95% dip 0. 5 periods, 30% dip 25 periods, > 95% interruptions 250 periods					
OTHERS	MTBF	6433.3K hrs min. Telcordia SR-332 (Bellcore) ; 1226.3K hrs min. MIL-HDBK-217F (25℃)									
	DIMENSION	PCB mounting style : 87*52*29.5mm (L*W*H) Screw terminal style : 109*52*33.5mm (L*W*H)									
	PACKING	PCB mounting style : 0.195Kg;60pcs/12.7Kg/0.94CUFT Screw terminal style :0.228Kg;50pcs/12.4Kg/0.56CUFT									
NOTE	1. All parameters NOT specially mentioned are measured at 230VAC input, rated load and 25℃ of ambient temperature. 2. Ripple & noise are measured at 20MHz of bandwidth by using a 12" twisted pair-wire terminated with a 0.1uf & 47uf parallel capacitor. 3. Tolerance : includes set up tolerance, line regulation and load regulation. 4. The ambient temperature derating of 3.5℃/1000m with fanless models and of 5℃/1000m with fan models for operating altitude higher than 2000m(6500ft). 5. The power supply is considered as an independent unit ,but the final equipment still need to re-confirm that the whole system complies with the EMC directives. For guidance on how to perform these EMC tests, please refer to "EMI testing of component power supplies." (as available on http://www.meanwell.com) ※ Product Liability Disclaimer : For detailed information, please refer to https://www.meanwell.com/serviceDisclaimer.aspx										


■ Block Diagram



■ Derating Curve





■ Output Derating VS Input Voltage



Mechanical Specification



Case No. IRM60 Unit:mm

• PCB mounting style (IRM-60)



AC/L, AC/N P/N diameter: 1 ϕ
+V, -V P/N diameter: 2 ϕ

• Screw terminal style (IRM-60-xxST)



Installation Manual

Please refer to : <http://www.meanwell.com/manual.html>